

RS02/RS03

NEW

Ergonomic Design

***Easy
Handling***



Ribbon Fiber Stripper

RS02/RS03



- 20% less gripping force compared to previous model
- Quicker Heating Time
- Bluetooth capability for wireless connection with Smartphones
- High capacity battery approx. 600times (RS03)
- Coating diameter available from 200 μ m to 400 μ m

RS02/RS03

SPECIFICATIONS

	RS02	RS03	RS03-80
Applicable optical fiber	Glass optical fibers		
Fiber count	1 to 12		Single
Cladding diameter	125μm		80μm
Coating diameter	200 to 400 μm		150 to 250 μm
Stripping length	Up to 35mm		
Typical heating time	3sec. 5sec. at Eco mode		
Standard heating temperature	100°C		
Fiber holder	FH-50series, FH-60series, FH-100series Except for FH-50-250		
Wireless connectivity	Bluetooth®4.1*1 OS:Android 5.0 or above, iOS 8.0 or above (iPhone6 or above)		
Dimensions	156(W)×49(D)×33(H)mm	156(W)×49(D)×37(H)mm	
Weight	185g	265g(with Battery)	
Power supply	100 to 240V AC with optional AC adapter, ADC-09A DC10~17V with external DC power supply : DC7.4V with Battery pack , BTR-12(Rechargeable Lithium-ion battery)		
Battery capacity	-	1620mAh : Typical 3.5h , 600 times at Eco mode	
Operating conditions	Temperature: -10 to 50°C, Humidity: 0 to 95% RH (Non-condensing)		
Storage conditions	Temperature: -20 to 60°C, Humidity: 0 to 95% RH (Non-condensing)		
Resistance feature	Shock resistance : 76cm (30inch) all surface drop(Telcordia GR -955-CORE) Rain resistance : H=10mm/hr for 10min(JIS C 0 034)		

※The Bluetooth wireless connection of this product is not guaranteed to work with all smartphones or other devices.

•Bluetooth® and Bluetooth logo is a registered trademark of Bluetooth SIG, Inc.



STANDARD PACKAGE

Description	Model	RS02	RS03	RS03-80
Main body	RS02	1pc	-	-
	RS03	-	1pc	-
	RS03-80	-	-	1pc
Battery pack	BTR-12	-	1pc	
DC power cord	DCC-11	1pc	Option	
AC adaptor	ADC-09A	Option	1pc	
AC power cord	ACC-xx	Option	1pc, selectable ACC ●08: Japan type ●09: USA type ●10: UK type ●11: EU type ●12: Australia type	
Instruction manual	M-RS02/03-E	1pc		
Hexagon wrench	HEX-01	1pc		
Brush	BRS-02	1pc		

OPTIONAL ITEMS

Description	RS02	RS03	RS03-80
Spacer		SPA-RS02-08	

STANDARD PACKAGE



Please visit **NEW** web site!

<https://www.fusionsplicer.fujikura.com>



Facebook

<https://www.facebook.com/FujikuraFusionSplicers>



twitter

<https://twitter.com/fujikurasplicer>

Specifications and descriptions are subject to change without prior notice. ©2017 Fujikura Ltd.

Fujikura Ltd.

1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan

Phone:+81-3-5606-1164 Fax:+81-3-5606-1534 <http://www.fujikura.com>

Fujikura Asia Ltd.

438A Alexandra Road, Block A Alexandra Technopark #08-03 Singapore 119967
Phone:+65-6-278-8955 Fax:+65-6-278-0965 <http://www.fujikura.com.sg>

Fujikura Europe Ltd.

C51 Barwell Business Park, Leatherhead Road, Chessington, Surrey KT9 2NY, UK
Phone:+44-20-8240-2000 Fax:+44-20-8240-2010 <http://www.fujikura.co.uk>

AFL

260, Parkway East, Duncan, SC29334, USA

Phone:+1-800-235-3423 Fax:+1-800-926-0007 <http://www.aflglobal.com>

Fujikura (China) Co., Ltd.

7th Floor, Shanghai Hang Seng Bank Tower, 1000 Lujiazui Ring Road, Pudong New Area, Shanghai, 200120 CHINA
Phone:+86-21-6841-3636 FAX +86-21-6841-2070